

Specification Sheet Tiles for Floors Medium

4,0/0,55,with 1mm IXPE RIGD-SPC

Technical details

Dimensions	610x610	
Wearlayer	0.55 mm	
Weight	ca. 8,10 kg / m ²	

Classification

	Property	Test Method Standard	Review in accordance with Standard
	Class 23 Heavily used domestic areas	EN ISO 10874	Living room, corridors
	Class 33 Heavily used commercial areas	EN ISO 10874	Offices, Shops, Hospitals
	I4F Click system	-	Simple and fast installation
	Reaction to fire	EN 13501-1	Bfl - s1
	Slip resistanced	EN 13893	DS
	Slip resistance level	DIN 51130	R9
	Light stability	ISO 105-B02	≥ 6
	Determination of resistance to stains chemical resistance	ISO 26987	Resistant
	Burning cigarette	EN 13999	Rating 3
	Formaldehyde emission	EN717-1	E1
	Residual Indentation	EN433/ISO 24343-1	≤0,1mm
	Dimensional stability	EN434/ISO 23999	≤0,1%
	Thermal resistance	EN 12667	0,050 (m ² K)/W
	VOC Emission	ISO 16000	A+
	TUV PROFI Cert.		Auditing by Institute EPH/Dresden

Notes:

* Technical changes reserved by Vanca Belgium.